Australian Journal of Basic and Applied Sciences, 9(11) May 2015, Pages: 657-663

ISSN:1991-8178

Australian Journal of Basic and Applied Sciences

Journal home page: www.ajbasweb.com

Video Recommendation based on user Behavior and Minimizes Storage

Naveen Vignesh Kumar S, Dhinakaran K, Dr. Dhanaseakaran D

Saveetha School of Engineering, Saveetha University, Thandalam-602105

ARTICLE INFO

Article history:
Received 12 March 2015
Accepted 28 April 2015
Available online 1 June 2015

Keywords:
The Profile Filtering Agent (PFA), Tag Cloud-based Cosine (TCC), support vector machines (SVMs), lazy associative classification (LAC).

ABSTRACT

Now a days we are facing lots of massive multimedia service in the internet most of the online video sharing website are facing lots of unrelated videos and spammer videos and also we cannot find the recommend videos as we needs and also it consumes the storage space in the database. There are lots of online sharing websites like YouTube,Rediff, 4Shared, Photobucket, Yahoo Video, Metacafe and Ning etc. all of these online sharing websites are used to recommend the videos based on the context process. Context procedure is where it used to mention the videos based in the users Characteristics, approach and mood and also it consumes giant computation. Content pollution might expose the trust of users on the system we offer a characterization of content, individual, and social attributes that facilitate distinguish every user category. On-line video sharing systems, out of that YouTube is that the most well liked, give options that enable users to post a video as a response to a discussion topic. These options open opportunities for users to introduce contaminated content, or just pollution, into the system. therefore we discover as an example, Spammers might post AN unrelated video as response to a preferred one, aiming at increasing the chance of the response being viewed by a bigger range of users. So to get user recommended video and also to reduce storage of unrelated video we have introduce user behavior recommended videos

© 2015 AENSI Publisher All rights reserved.

To Cite This Article: Naveen Vignesh Kumar S, Dhinakaran K, Dr. Dhanaseakaran D, Video Recommendation based on user Behavior and Minimizes Storage. ***Aust. J. Basic & Appl. Sci.,*** *9(11): 657-663, 2015*

INTRODUCTION

Online video sharing systems, out of that YouTube is that the most well liked, offer options that enable users to post a video as a response to a discussion topic. These options open opportunities for users to introduce impure content, or just pollution, into the system. Thus we discover for example, spammers might post associate degree unrelated video as response to a well-liked one, aiming at increasing the chance of the response being viewed by a bigger variety of users.

Personalization makes it fast and straightforward to dynamically realize a video supported a user's preference within the variety of video, and permits easy accessibility. For this personalization a recommendation system is important and also storage because in every database not much recommended videos are also consuming some storage space in the database to reduce that and also make the user's personalized video as safe.

In the propose PDPR system personalization technique collects and analyzes the viewing patterns, such as: the target user's viewing pattern for contents, applied math info for the general user's viewing patterns, a user's non-public profile or preference info through the analysis of a user's computing surroundings, a communication service, and also the most well-liked device sorts like an itinerant, laptop computer, etc. A content-based recommendations system recommends the foremost seemingly matched item, then compares the advice list to a user's previous input file or compared to preference things. A content-based recommendations system relies on info looking and usually uses a rating technique that is employed within the info looking. The rating technique calculates a user's preference info and things in an exceedingly recommendation list. It recommends the foremost seemingly program in an exceedingly user's profile. This technique has the advantage with simply adopt in recommendation result and modify additional quickly recommendation. However its issues with distinction result and economical discuss with acceptable rating configuration.

Related works:

In web User Created Contents (UCC) and on-line Digital Video (ODV) Agrawal (1993) enabled the fast increase of on-line Video and programs

Corresponding Author: Naveen Vignesh Kumar, UG Scholar, Saveetha School of Engineering, Saveetha University, Thandalam-602105

which may be hand-picked by shoppers. This wasn't expected once we contemplate the standard Video technologies and policies. Attributable to this paradigm changes, thousands of video and programs square measure currently on the market to shoppers. Within the existing restricted content suppliers existed, like commissioned broadcasting corporations and a tiny low range of video and satellite broadcasting operators. Therefore the quantity of picture and programs were restricted. Itbecame troublesome and time intense to search out a noteworthy picture video and program via the remote or channel guide map. To refine the channel choosing processes and to satisfy the consumer's necessities, we have a tendency to propose the web Video Recommendation (ODV) (Benevenuto, 2001) system beneath a cloud computing setting. The projected ODV system analyzes and uses the viewing pattern of shoppers to change the program recommendations, and to expeditiously use computing resources. A projected framework for recommending on-line videos operates by constructing user profiles as a combination of tag clouds and generating recommendations in line with similar viewing patterns.

The projected personalization methodology collects and analyzes the viewing patterns, like: the target user's viewing pattern for contents, applied mathematics info for the general user's viewing patterns, a user's personal profile or preference info through the analysis of a user's computing setting, a communication service, and enforced in pc, however in future we have a tendency to most well-liked the Mobile device.

Internet users post an oversized range of video clips on Video-sharing websites and social network applications on a daily basis (Benevenuto, 2001). The video content is also duplicating, similar, related, or quite totally different. Facing billions of transmission Webpages, on-line user's square measure sometimes having a tough time finding their favorites. Some video-sharing websites suggest video lists for finish users per video classification, video description tags, or looking at history. However, these recommendations don't seem to be correct and square measure invariably not in step with the top users' interests. To enhance this, some websites additionally give users with program to go looking their desired videos quickly. However, looking out is predicated on the keywords.

Cloud-based mobile multimedia system recommendation system which might cut back network overhead and speed up the advice method theuser's square measure classified into many teams in step with their context varieties and values. With the correct classification rules, the context details aren't necessary to reckon, and therefore the immense network overhead is complete[T. Rodrigues(2009)]. Furthermore, user settings, user relations, and user outlines square amount collected from video-sharing websites to come up with multimedia system recommendation. That the planned approach will advocate desired services with high preciseness, high recall, and low response delay. User clusters square measure collected rather than elaborated operator profiles. To avoid the explosion of network overhead, user-behavior-based agglomeration is performed initial, and therefore the collectors calculate user clusters in step with the agglomeration rules so report the user cluster to the recommended solely.

System design and implementation details:

User Side:

User or End user is that the one whoreally consuming the product. User should register his or her name, mail id, user name, password and he or she mentioned the characteristic of favorite video that they want to watch it. The authentication key will be send to the mail id that he or she mentioned in the registration. Only valid user can able to access the respective video. After that the user can able to login with the User name and Password that registered and only the user categorized video will be displayed to user login. If user want to see some other video other than the user categorized , the user want to search in the Global search box where user can able to find some other video than the user categorized video (Boll S 2009). The user can also keep the key word search so that user's favorite video can be able to search very easy. The system design and implementation details is shown in the Fig1.1.In the system design and implementation there are two side User and provider side. The user side is very important because the user should like videos if not the provider will be removed from his or her channel from the website. User should be authenticated user the user should login with the appropriate details so that the user will be good appropriate user login. And also login process also will be done easy the secrete key is send to the user mail ID so that it give more security to the user.



Fig. 1.1: Shown the System design and implementation details.

Provider Side:

Provider is the one who actually provides a way of subsistence one that produces one thing, like a service, available, etc. provider is use to provide the video to the end user or the one who actually consuming the product. Without provider there is no user. Provider should be upload the video as per the character that mean the provider should upload the cartoon video to cartoon character. This is shown in the fig1.1 about the provider side.

Provider also should be registered about the provider details like provider name, name of user name, and password and mail id of the provider so that only valid provider can be accessed the data and provided the good data.by using the login of the provider the provider can able to login the his or her user name and password the provider so able to upload the good categorized video so that user can able to watch good related video that asked from the provider. Suppose if provider misuse the data or a video that giving to the user. The user can able to report to the Admin about the misuse of the provider action of unrelated video or if the provider give no categorized video to the user the user can able to block the provider videos form his or her login page, if the all the user dislike the video provided by the provider the video can be removed from the website (T. Rodrigues 2009)

Normally the most online video sharing websites like the YouTube,Daily Motion, Flickr, Youku, Rediff, 4Shared, Photobucket, Yahoo Video, Metacafe and Ning etc. so these are some online sharing video. The main drawback in the above on-line video sharing is that if unrelated video is posted by the provider the user will only dislike the video posted by provider the video will be remind on the recommended video list or user can able to be disappear the unrelated video or spammer video if the user search in the search about the video or key word of the video the video can will be displayed so that it is very difficult to the user to see on the recommended video and also many online video sharing websites if the user don't like the video or some unrelated video the Admin and Provider are have authority to remove so that it is also occupies lots of storage space . That's where we have introduce the new website like this the user can able to categorized the video that he or she want to watch the video and also the user can also able to remove the un-recommended, unrelated video or Spammer video can be removed .

Experimental and result:

In the experimental and result there are some modules are used they are Private storage formation, User Recommender system, Content filtering and Reusability and Spammer detections are discussed in below topics.

(a) Private storage Formation:

We create a non-public space for storing for each suppliers in our media storage Server. At the time of making asupplier account the video space for storing are going to be allotted to the supplier. That memory of the space for storing isn't a hard and fast, it will large-scale storage .From this format we will uphold videos confidentially (Caglayan.A, M 1997).

The non-public Storage Formation (PSF) monitors the target consumer's identity profile. The Popular Fight Front supports organization, scheduling, security, privacy management of the buyer profile, and also the needed resources. Within the projected system, every intelligent device one by one transfers weblog history to the Popular Struggle Front. The Profile Manager (PM) then analyzes the combined weblog, and creates the buyer profile supported this weblog. The projected Popular Struggle Front will determine the consumer's preference during a short quantity of your time, and supply a suggested channel list at initial time. Labels may be shared in diversehabits in which to characterize AN entity of User interest. Tag info is mentioned as a tag that is typically displayed in alphabetical order and visually weighted by font size. The Storage Formation offers developers and systems directors straightforward thanks to produce and manage a set of connected AWS resources, provisioning and change them in an orderly and sure fashion.

You can use AWS Formation's sample templates or produce your own templates to explain the AWS properties, and any related addictions or runtime parameters, needed to run your application[Chien Y.-H.(1999)]. You don't have to be compelled to comprehend the order during which AWS services have to be compelled to be provisioned or the subtleties of the way to create those dependencies work. Non-publicstorage Formation takes care of this for you. Once deployed, you'll modify and update the AWS resources during a management led and sure manner permitting you to version management your AWS infrastructure within the same manner as you version control your code.



Fig. 1.2: Private storage for a Service provider.

The fig 1.2 showing the private storage for the provider user or provider login with the respective ID

if the provider is a new user then registration process is done there and after the registration process is done the private storage is allocates for a particular user or a provider then the provider can able to upload the respective videos to as categorized the storage of the user all the details are stored in the database .The details are storage space of a particular provider

You can deploy and update a model and its associated assortment of resources (called a stack) via the AWS Management Console, storage Formation program line tools or genus Apis. Storage Formation is accessible at no extra charge, and you pay just for the AWS resources required to run your applications.

(b) User Recommender system:

A content-based recommendations system recommends the foremost seemingly matched item, then compares the advice list to a user's previous computer file or compared to preference things. A content-based recommendations system relies on info looking out and usually uses a rating methodology that is employed within the info looking out. To measures for computing computing the user similarity, particularly tag cloud-based cos (TCC) and tag cloud similarity rank (TCSR). The Profile Filtering Agent (PFA) generates a personalized channel profile supported the accumulated viewed content list by employing a content based mostly filtering.

Users will advocate the videos to the user itself, at the time of user profile creation. The suggested videos post to the consumer profile as video tag system. The video tag is generated supported the user suggested.

Recommender systems or recommendation systems (sometimes commutation "system" with an` equivalent word like platform or engine) area unit a taxonomic category of knowledge filtering system that obtain to predict the 'rating' or 'preference' that a user would offer to Associate in Nursing item (such as music, books, or movies) or social component (e.g. folks or groups) that they had not nevertheless thought of, employing a model engineered from the characteristics of Associate in Nursing item (content-based approaches) Recommender systems became very common in recent years. Some samples of such systems.

When viewing a product on Amazon.com, the shop can advocate further things supported a matrix of what different shoppers bought together with the presently elite item. Pandora Radio takes Associate in nursing initial input of a song or musician and plays music with similar characteristics (based on a series of keywords attributed to the inputted creator or piece of music). The positionsproduced by Pandora isadvanced through user feedback (emphasizing or deemphasizing bound characteristics).

Netflix suggestions calculations of flicks that a user may wish to watch supported the user's previous ratings and looking habits (as compared to the behavior of different users), conjointly taking into consideration the characteristics (such because the genre) of the film.

In Fig 1.3 showing the user recommended videos based on the users pattern and context search.



Fig. 1.3: User recommended videos.

(c)Content filtering and Reusability:

A content-based recommendations system recommends the foremost possible matched item. To compares the advice list to a user's previous input file or compared to preference things (Freund Y, 1998). A content-based recommendations system relies on info looking and usually uses a rating methodology that is employed within the info looking. The Profile Filtering Agent (PFA) creates a customized channel profile supported the accumulated viewed content list by employing a content based mostly filtering.

On the web, content filtering (also referred to as info filtering) is that the use of a program to screen and exclude from access or convenience sites. Content filtering is employed by firms as a part of net firewall computers and additionally by information processing system house owners,

particularly by folks to screen the content their youngsters have access to from a laptop (Freund Y, 1998).

Content filtering sometimes works by specifying character strings that, if matched, indicate undesirable content that's to be screened out. Content is often screened for sexy content and typically additionally for violence- or hate-oriented content. Critics of content filtering programs show that it's not troublesome to accidentally exclude fascinating content.

Content filtering and also the merchandise that provide this service is divided into net filtering, the screening of websites or pages, and video filtering, the screening of video for spam or alternative objectionable content.



Fig. 1.4: filtering of videos based on the users behavior.

A Web filter may be a program that may screen AN incoming online page to see whether or not some or all of it shouldn't be showed the user. The filter checks the origin or content of an internet page against a collection of rules provided by company or one who has put in the online filter.

(d)Spammer detections:

Spammer detection the meaning for the spammer detection is unrelated things. In the Normally many websites there are lots of unrelated videos will be displayed when we search in some respective topics. It is not a user or consumer mistake it is a promoter or provider mistake that means the provider is used to uploading unrelated videos in the respective topics (Seung, E, 1997).

Spammers might post associate unrelated video as response to a preferred one. We have a tendency to discover the spammer'svictimization client suggestion personal storage formation method. Lazyassociative classification algorithms to mechanically discover spammers.Classifying them as spammers, promoters, and legit users.Victimization our take a look at assortment, we offer a characterization of content, individual, and social attributes that facilitate distinguish every user category. We have a tendency to then investigate the practicability of victimization supervised Classification algorithms to mechanically discover spammers and promoters, and assess their effectiveness in our take a look at assortment. Analyzed a range of video, individual and social attributes that mirror the behavior of our sampled users, aiming at drawing some insights into their relative discriminatory power in characteristic legitimate users, promoters, and spammers.

Fourth, victimization an equivalent set of attributes, that square measure supported the user's profile, the user's social behavior within the system, and therefore the videos denote by the user further as her target (responded) videos, we have a tendency to investigated the practicability of applying supervised learning

Methods for characteristic the 2 unreal styles of polluters.We have a tendency to take into account 2 progressive supervised classification algorithms, namely, support vector machines (SVMs) and lazy associative classification (LAC). We have a tendency to evaluate each algorithm over our take a look at assortment, finding that each techniquecan effectively determine the bulk of the promoters and spammers.

So to Personalization makes it quick and easy to dynamically find a video based on a user's preference in the number of video, and enables easy access. For this personalization a recommendation system is necessary



Fig. 1.5: Spammer detection.

Conclusion:

The main purpose of user behavior video sharing is our system recommends channels based on their viewing pattern and interests. We can able to remove unrelated videos from our login site and also able to categorized favorite video as per our wish .The users just need to select the channel that they want to watch and as much as user give dislike to a particular videos the videos will be removed from the website so that the storage space for a spammer videos will free. The main aim is to reduce the storage. Because storage is the main issue facing by many online sharing websites. It is not restricted for a user to watch recommended channel and we believe that User recommended video will be use full for the kids who want to play and learn from the internet.

REFERENCES

Agrawal, T. Imielinski and A. Swami, "1993. Mining association rules between sets of items in large databases," in Proc. Int. Conf. Management Data, pp: 207–216.

Benevenuto, F., C. Costa, M. Vasconcelos, V. Almeida, J. Almeida and M. Mowbray, 2006. "Impact of peer incentives on the dissemination of polluted content," in Proc. ACM SAC, pp: 1875–1879.

Benevenuto, F., G. Magno, T. Rodrigues and V. Almeida, 2010. "Detecting spammers on twitter," in Proc. Annu. CEAS Conf, pp: 1–9.

Benevenuto, F., T. Rodrigues, V. Almeida, J. Almeida and K. Ross., 2009. "Video interactions in online video social networks," ACM Trans. Multimedia Comput., Commun. Appl. (TOMCCAP), 5(4): 1–25.

Benevenuto, F., T. Rodrigues, V. Almeida, J. Almeida, and M. Gonalves, 2009. "Detecting spammers and content promoters in online video social networks," in Proc. Int. ACM Conf. Res. Develop. Inf. Retrieval (SIGIR), pp: 620–627.

Benevenuto, F., T. Rodrigues, V. Almeida, J. Almeida, M. Gonalves and K. Ross, "Video pollution on the web," First Monday, 15(4): 1–20.

Boll, S., 2007. "Multitube—Where web 2.0 and multimedia could meet," IEEE MultiMedia, 14(1): 9–13.

Breese, J.S., D. Heckerman and C. Kadie, 1998. "Empirical Analysis of Predictive Algorithms for Collaborative Filtering," Proc. 14th Conf.Uncertainty in Artificial Intelligence.

Brin, S. and L. Page, 1998. "The anatomy of a large-scale hypertextual web search engine," in Proc. Int. WWW Conf, pp: 107–117.

Buhmann, M.D., 2001. "Approximation and Interpolation with Radial Functions," Multivariate Approximation and Applications, N. Dyn, D. Leviatan, D. Levin, and A. Pinkus, eds., Cambridge Univ. Press.

Burke, R., 2000. "Knowledge-Based Recommender Systems," Encyclopedia of Library and Information Systems, A. Kent, ed., vol. 69, Supplement 32, Marcel Dekker.

Caglayan, A., M. Snorrason, J. Jacoby, J. Mazzu, R. Jones and K. Kumar, 1997. "Learn Sesame—A Learning Agent Engine," Applied Artificial Intelligence, 11: 393-412.

Chaudury, S. and U. Dayal, 1997. "An Overview of Data Warehousing and OLAP Technology," ACM SIGMOD Record, 26(1): 65-74.

Chien, Y.H. and E.I. George, 1999. "A Bayesian Model for Collaborative Filtering," Proc. Seventh Int'l Workshop Artificial Intelligence and Statistics.

Claypool, M., A. Gokhale, T. Miranda, P. Murnikov, D. Netes and M. Sartin, 1999. "Combining Content-Based and Collaborative Filters in an Online Newspaper," Proc. ACM SIGIR '99 Workshop Recommender Systems: Algorithms and Evaluation, Aug.

Comscore Americans Viewed 12 Billion Videos Online in May2008. [Online]. Available:http://www.comscore.com/press/release.asp?press=2324

Freund, Y., H.S. Seung, E. Shamir and N. Tishby, 1997. "Selective Sampling Using the Query by Committee Algorithm," Machine Learning, 28(2-3): 133-168.

Freund, Y., R. Iyer, R.E. Schapire and Y. Singer, 1998. "An Efficient Boosting Algorithm for Combining references," Proc. 15th Int'l Conf. Machine Learning.

New York Times, Accessed in July/2010 Uploading the Avantgarde.[Online]. Available:http://www.nytimes.com/2009/09/06/magazine/06FOB-medium-t.htm

Youtube Fact Sheet, [Online]. Available: http://www.youtube.com/t/fact_sheet